



enoline 4
REF



enoline 8
REF - WINE CARD

THE ENOLINE CLASSIC SERIES HAS GROWN TO BE THE BEST SELLER WORLDWIDE THANKS TO IT'S VERSATILITY. IT IS AVAILABLE IN BOTH 4 OR 8 BOTTLE VERSIONS WITH A DEPTH OF 20 CM THAT MAKES IT ADAPTABLE TO ALL VENUES.

enoline

- **Available models:**
 - enoline 4 ref (4 bottles in a row)
 - enoline 8 rt / ref / dual (8 bottles in a row)
- **Wine temperature:**
 - room temperature
 - refrigerated: from 7 to 18°C (from 45 to 65°F)
 - dual: 4 chilled bottles + 4 climate controlled bottles
- **Use and system activation:** behind the counter (without wine card) or self-service (with wine card).
- **Gas supply:** food grade nitrogen or argon (cylinder or generator non included).
- **Servings:** 1 or 3 configurable volumes with membrane keys.
- **Display (wine card systems only):** each bottle position has a 4 digit price display and a 16 character LCD display for general card information.
- **Materials:** stainless steel with baydur black polyurethane lid.
- **Cooling system:** by refrigerator compressor.
- **Condensate drainage:** required.
- **Compressor positioning:** right or left side.
- **Lighting:** with static light LED.
- **Bottles lifting system:** pneumatic pistons which can be operated with air or nitrogen .
- **Positioning:** refrigerated and dual models require a 30 cm (12") distance from compressor side and 5 cm (2") from the rear.
- **Wine card type:** chip card (SMART card). Finger print, magnetic stripe or bar code customizable upon request.
- **Modules interfacing:** LAN network, TCP/IP protocol.

models	L	H	D	weight	electrical requirements
enoline 4 REF	750 mm (29.5")	643 mm (25.2")	200 mm (8")	40 kg (88.2 lbs)	115 o 230 V – 150 W
enoline 8 RT	970 mm (38.2")	643 mm (25.2")	200 mm (8")	45 kg (99.2 lbs)	115 / 230 V – 30 W
enoline 8 REF	1190 mm (47")	643 mm (25.2")	200 mm (8")	65 kg (143.3 lbs)	115 or 230 V – 150 W
enoline 4+4 DUAL	1190 mm (47")	643 mm (25.2")	200 mm (8")	65 kg (143.3 lbs)	115 or 230 V – 150 W